

OHIO



HARSCO
MINERALS

Pulverized Industrial Co-Product Agricultural Liming Material

Guaranteed Analysis (Dry Weight Basis)

Minimum Percent Calcium	24
Minimum Percent Magnesium	5.5
Minimum Total Neutralizing Power (by titration)	80. *
Minimum Effective Neutralizing Power	1,500 lbs/ton
Minimum Percent Passing #8 Mesh Screen	100
Minimum Percent Passing #20 Mesh Screen	95
Minimum Percent Passing #60 Mesh Screen	78
Minimum Percent Passing #100 Mesh Screen	65
Maximum Percent Moisture Content	20 **
Average pH (paste)	pH 12

* Expressed as percent Calcium Carbonate

Ohio Registration: Environmental Protection Agency No. 07-0057, Department of Agriculture No. 91799 (PA), 91800 (KY)

Recommended Application Rates: Specific recommendations for application rates to raise pH should be obtained from soil testing. The lifetime loading rate should not exceed 83 dry tons per acre. Excessive application of AgrowSil™ or any liming agent can result in soil pH higher than desirable for plant growth. For Spreaders: Bulk Density is 93 lbs/ft³

Storage Recommendations: Store AgrowSil™ in a dry place not in direct contact with ground water or surface water. Harsco Minerals recommends that AgrowSil™ be applied within 30 days of purchase to avoid formation of clumps.

AgrowSil™ is not to be used as an animal feed additive. Harsco Minerals recommends waiting 30 days after application before allowing grazing.

CAUTION: May cause eye and respiratory tract irritation. Avoid contact with eyes. Avoid breathing dust. Use with adequate ventilation.

FIRST AID: EYE – Flush immediately with plenty of water for at least 15 minutes. Call a physician.
INHALATION – Remove to fresh air.

Additional Information: Harsco Minerals guarantees that the AgrowSil™ product characteristics listed above are verified to be in compliance at the time of production per each lot of AgrowSil™. AgrowSil™ product is sampled as produced and is tested by an approved independent laboratory. Harsco Minerals cannot guarantee product characteristics (i.e. moisture, grain size) that are affected by long term storage or by improper care, handling, segregation, and storage by distributors or end users.

A certified analysis of your AgrowSil™ order is available upon request.

AgrowSil™ produced by Harsco Minerals International
(Pulverized Slag Co-Product from the recovery of stainless steel from stainless steel slag.)

**AgrowSil™ is provided at as-produced moisture contents ranging from about 14% to 20%.

HARSCO
MINERALS

359 North Pike Rd, Sarver, PA 16055
Office: 724-353-2300
Fax: 724-353-0057
Toll Free: 800-850-0527
www.harscominerals.com

Product Information